


C-HRV 313-L

High efficiency and flat design

Description


The C-HRV 313-L counterflow heat exchanger has a low pressure drop with moderate thermal efficiency. Its narrow width makes it ideal for ceiling installation. The C-HRV 313-L offers high quality, long life and low maintenance and can be custom designed to meet your specific needs.




Product benefits

- Cleanable, hygienic, mold and bacteria resistant
- Standard: Condensation drain holes
- Option: Rib, Fire protection grid
- Available heights: 50 – 400 mm (in 5mm steps)
- Leakage: <1% of nominal flow rate, 100% leakage tested
- Material resistance: -20 °C – +50 °C


Product dimensions (mm)



Temperature efficiency



Pressure drop



Based on test conditions following NEN-EN 308:2022 (intake air: temp. 5 °C, humidity 70 %; extracted air: 25 °C, humidity 25 %) Calculate your specific conditions with our CORE Online Calculator.

Standards

- Hygiene Standard
 - VDI6022 sheet 1 (01/2018)
 - ÖNORM H6021 (01/2023)
 - SWKI VA104-01 (01/2019)
- Fire Standard
 - EN DIN13501-1 (Class E)
 - ISO 11925 (Class E)
- Quality Management
 - DIN ISO 9001: 2015

Weights (kg)

Typ	kg
HRV313-H100-LR	0,64
HRV313-H200-LR	1,12
HRV313-H300-LR	1,61
HRV313-H400-LR	2,09